



AV 2 poles 3000 rpm-50Hz / 3600 rpm-60Hz

	Model Type	Devir (Rpm) (Hz)		Santrifüj Kuvveti Centrifugal Force (Kg/F) 50 Hz	Giriş Gücü Input Power (W) 50 Hz	Voltaj Voltage (V) 50 Hz	Nominal Akım Nom. Current (Amp) 50 Hz
		50 Hz	60 Hz				
three-phase	AV-2T	3000	3600	22	22	400	0,12
	AV-4T	3000	3600	44	40	400	0,18
	AV-6T	3000	3600	65	40	400	0,18
single-phase	AV-2M	3000	3600	22	22	220	0,12
	AV-4M	3000	3600	44	40	220	0,18
	AV-6M	3000	3600	65	40	220	0,18
three-phase	AV-2	3000	3600	22	22	220	0,12
	AV-4	3000	3600	44	40	220	0,18
	AV-6	3000	3600	65	40	220	0,18

(*) Working moment = 2x static moment

Ia / In = başlangıç akımı ile maksimum akım arasındaki oran./ ratio between start-up current and maximum current.



AV 2 poles 3000 rpm-50Hz / 3600 rpm-60Hz

TP TC 012/2011
II 2GD Ex tb IIIC (T 120 OC) Db, IP 66 - Ex eb IIB T5 Gb IP 66 - Tamb (-20 °C / +50 °C)

Model Type	Gövde Ölçüleri - Overall Dimensions (mm)																	
	A	B	C	ØD	E1-E2	F1-F2	G	H1	H2	H3	I1	I2	I3	J	K	L	M	N
three-phase AV-2T	182	123	72	61	24-40	62-74	60	85	92	106	9	7	7	45	37	31.5	92	12
three-phase AV-4T	182	123	72	61	24-40	62-74	60	85	92	106	9	7	7	45	37	31.5	92	12
three-phase AV-6T	202	123	72	61	24-40	62-74	60	85	92	106	9	7	7	55	37	31.5	92	12
single-phase AV-2M	182	123	72	61	24-40	62-74	60	85	92	106	9	7	7	45	37	31.5	92	12
single-phase AV-4M	182	123	72	61	24-40	62-74	60	85	92	106	9	7	7	45	37	31.5	92	12
single-phase AV-6M	202	123	72	61	24-40	62-74	60	85	92	106	9	7	7	55	37	31.5	92	12
three-phase AV-2	182	123	72	61	24-40	62-74	60	85	92	106	9	7	7	45	37	31.5	92	12
three-phase AV-4	182	123	72	61	24-40	62-74	60	85	92	106	9	7	7	45	37	31.5	92	12
three-phase AV-6	202	123	72	61	24-40	62-74	60	85	92	106	9	7	7	55	37	31.5	92	12

